

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

1. (original): An adaptive variable-length coding method whereby quantized orthogonal transform coefficients are scanned in a zigzag pattern, are modified into run, level data and then are variable-length coded in a coding system for image data, said method comprising the steps of:

setting a plurality of variable-length coding tables having different patterns of a regular region and an escape region according to statistical characteristics of said run, level data;

selecting one of said plurality of variable-length coding tables according to intra/inter mode information of the currently processed block, zigzag scanning position and quantization step size; and

variable-length coding the orthogonal transform coefficients according to said selected variable-length coding table, wherein said selecting step has the selecting range of a plurality of variable-length coding tables having different patterns of a regular region and an escape region according to said intra/inter mode information of the currently processed block.

2. (original): The adaptive variable-length coding method as claimed in claim 1, wherein said variable-length coding table is selected in accordance with said zigzag scanning position and quantization step size within the range determined by the corresponding mode.

3. (original): The adaptive variable-length coding method as claimed in claim 1, wherein data of said escape region of said variable-length coding table selected in said variable-length-coding step is coded into data having variable run-length and level-length.

4-8. (canceled).

9. (currently amended): An adaptive variable-length coding method in which quantized orthogonal transform coefficients are scanned in a predetermined pattern, and then are variable-length coded in a coding system for image data, said method comprising the steps of:

setting a plurality of variable-length coding tables;

selecting one of said plurality of variable-length coding tables according to intra/inter mode information, scanning position and quantization step size, wherein said plurality of variable-length coding tables comprise:

a table selectable for an alternating-current (AC) component of an intra mode that is different from a table selectable for an inter mode, and

a table selectable for a direct-current (DC) component of said intra mode; and variable-length coding said quantized orthogonal transform coefficients according to said selected variable-length coding table; ~~The adaptive variable-length coding method of claim 18,~~

wherein said variable-length coding tables have different patterns of a regular region and an escape region.

10. (original): The adaptive variable-length coding method as claimed in claim 9, wherein said variable-length coding table is selected in accordance with said scanning position and quantization step size within the range determined in accordance with said intra/inter mode information.

11. (original): The adaptive variable-length coding method as claimed in claim 9, wherein data of said escape region of said variable-length coding table selected in said variable-length-coding step is coded into data having variable run-length and level-length.

12-19. (canceled).

20. (currently amended): An adaptive variable-length coding method in which quantized orthogonal transform coefficients are scanned in a predetermined pattern, and then are variable-length coded in a coding system for image data, said method comprising the steps of:

setting a plurality of variable-length coding tables;

selecting one of said plurality of variable-length coding tables according to intra/inter mode information, scanning position and quantization step size, wherein:

said selecting step has the selecting range of a plurality of variable-length coding tables, and

said plurality of variable-length coding tables comprise:

a table selectable for an alternating-current (AC) component of an intra mode that is different from a table selectable for an inter mode; and

a table selectable for a direct-current (DC) component of said intra mode; and
variable-length coding said quantized orthogonal transform coefficients according to said selected variable-length coding table; ~~The adaptive variable-length coding method of claim 19,~~

wherein said variable-length coding tables have different patterns of a regular region and an escape region.

21. (previously presented): The adaptive variable-length coding method as claimed in claim 20, wherein said variable-length coding table is selected in accordance with said scanning position and quantization step size within the range determined in accordance with said intra/inter mode information.

22. (previously presented): The adaptive variable-length coding method as claimed in claim 20, wherein data of said escape region of said variable-length coding table selected in said variable-length-coding step is coded into data having variable run-length and level-length.

23-24. (canceled).